

## 旋转式凹版电镀设备 RNB 7-250/1-6-001

## Rotational Reverse Plating Plant RNB 7-250/1-6-001

前视图 Front view



后视图 Rear view



1. 操作控制和调节装置(PRS) Process control and regulation unit (PRS)
2. 旋转式凹版电镀装置(RBE) Rotational reverse-plating unit (RBE)
3. 镀厚镍装置 (DVE, 3 台), 每台带有两个电镀站 Thick-nickel plating unit (DVE, 3 pcs) with two electro-plating stations each
4. 1400L 氨基磺酸镍电镀液的储存池(EVB) Electrolyte storage tank (EVB) for 1400 l nickel sulfamate electrolyte



用于调整和预设槽及操作参数，操作流程和操作编程的终端操作触摸屏  
Touchscreen operators' terminals for adjustment and pre-set of the bath and process parameters, process sequence control and process programming

可根据客户要求设置屏幕、功能和操作语言。  
Screen layouts, functions and operational languages to customers' specifications possible.



#### 旋转式凹版电镀装置 RBE

#### Rotational reverse-plating unit RBE

- 一个带有盖子的旋转电镀容器
- 1 rotational plating vessel with lid
- 带有膜片阀的流量计，用于调节电解液流量
- Flow meter and diaphragm valve for electrolyte flow regulation
- 旋转 最大 500 转每分 Rotation max. 500 rpm
- 一个旋转式凹版电镀调控装置 RBS 10A-45/001
- Rotational reverse-plating control RBS 10A-45/001

#### 镀厚镍装置 DVE 2/56-56-50/001

#### Thick-nickel plating unit DVE 2/56-56-50/001

- 2 个带有周边抽吸装置的电镀槽
- 2 electro-plating tanks with rim exhaustion
- 2 个水平旋转装置 2 horizontal rotation units
- 2 个镀厚镍调控装置 DVS 10A-45/0012
- thick-nickel plating controls DVS 10A-45/001
- 带有内置驱动调控装置 with built-in motor control



旋转式凹版电镀装置装有凹模(最大模外径 250mm)

Rotational reverse-plating fixture  
With reverse-plating mould  
max mould outer Ø 250 mm)



阳极棒系统(组件)  
Anode rod system  
(components)



电镀金刚石成型修整滚轮  
Diamond profile dressing roller